

NUTECH BOLTLESS LOADING CAPACITY (MEDIUM DUTY)

No	Height	Depth	Width	Loading Capacity/Level (Kg)	Boltless Post Loading Capacity
1	1786	300	750	250	1500
2	1786	300	900	250	1500
3	1786	300	1190	250	1500
4	1786	300	1500	250	1500
5	1786	300	1800	170	1500
6	1786	300	2400	140	1500
7	1786	400	750	250	1500
8	1786	400	900	250	1500
9	1786	400	1190	250	1500
10	1786	400	1500	250	1500
11	1786	400	1800	170	1500
12	1786	400	2400	140	1500
13	1786	580	750	250	1500
14	1786	580	900	220	1500
15	1786	580	1190	250	1500
16	1786	580	1500	200	1500
17	1786	580	1800	170	1500
18	1786	580	2400	140	1500
19	2090	300	750	250	1500
20	2090	300	900	250	1500
21	2090	300	1190	250	1500
22	2090	300	1500	250	1500
23	2090	300	1800	170	1500
24	2090	300	2400	140	1500
25	2090	400	750	250	1500
26	2090	400	900	250	1500
27	2090	400	1190	250	1500
28	2090	400	1500	250	1500
29	2090	400	1800	170	1500
30	2090	400	2400	140	1500
31	2090	580	750	250	1500
32	2090	580	900	220	1500
33	2090	580	1190	250	1500
34	2090	580	1500	200	1500
35	2090	580	1800	170	1500
36	2090	580	2400	140	1500
37	2394	300	750	250	1500
38	2394	300	900	250	1500
39	2394	300	1190	250	1500
40	2394	300	1500	250	1500
41	2394	300	1800	170	1500
42	2394	300	2400	140	1500
43	2394	400	750	250	1500
44	2394	400	900	250	1500
45	2394	400	1190	250	1500
46	2394	400	1500	250	1500
47	2394	400	1800	170	1500
48	2394	400	2400	140	1500
49	2394	580	750	250	1500
50	2394	580	900	220	1500
51	2394	580	1190	250	1500
52	2394	580	1500	200	1500
53	2394	580	1800	170	1500
54	2394	580	2400	140	1500

Thickness

1. Post : 1.2 mmT
2. Beam (300, 400, 450, 580, 750, 900) : 1.0mmT
3. Beam (1190, 1500, 1800, 2400) : 1.2 mmT

Post Height Standard :

- 722, 798, 988, 1786, 2090 and 2394